

# xFUME® PRO Fume Extraction Torch

270/350/500 Amp Torches

Ordering Instructions for Complete Torches

XP	3	15	H - 35	L	L	S		
Model	Amp	Cable Length	Fume Nozzle (Shroud)	Wire Size	Cable Type	Back End	Trigger	Custom Options
XP - xFUME® PRO								<b>Custom</b> 2 - 2" Longer
<b>Amperage</b>							<b>Trigger</b>	
2 - 270 Amp (Air-cooled)							S - Standard	
3 - 350 Amp (Air-cooled)							E - Extended	
5 - 500 Amp (Water-cooled)							<b>Back End</b>	
<b>Cable Length</b>							E - Euro	
15 - 15 Feet							HT - Tweco 4	
20 - 20 Feet							L - Lincoln Ext Gas	
25 - 25 Feet							L1 - Lincoln 10, 74 & 84 Series	
<b>Fume Nozzle (Shroud)</b>							L2 - Lincoln Power MIG	
H - High-flow Threaded Tapered (Standard)							M - Miller	
HR - High-flow Threaded Reverse Suction (350/500A only)							<b>Cable Type</b>	
HS - High - Flow - Threaded Tapered Steel (350/500A only)							L - Lightweight (Standard)	
							C - Full Copper (270+ 350A Only)	
							<b>Wire Size</b>	
							.035 Inches	
							.045 Inches	
							.052 Inches	
							.062 Inches (Water Cooled Only)	



ABICOR BINZEL USA, inc.  
 650 Medimmune Court, Suite 110  
 Frederick, MD 21703  
 Phone: 800.542.4867  
 Fax: 301.846.4497  
 E-Mail: customerservice@abicorusa.com

[www.binzel-abicor.com](http://www.binzel-abicor.com)